

DOLCECLIMA EASY 10 P

The portable air conditioner in console format



CONSOLE FORMAT:

Position it anywhere in your home



SILENT SYSTEM

The most silent of the range



TOUCH DISPLAY

LED display and touch controls



REMOTE CONTROL INCLUDED

Even simpler to manage

FEATURES

Nominal cooling capacity: 2,4 kW⁽¹⁾

Energy Class: A⁽¹⁾

Rated energy efficiency index: EER 2,6⁽¹⁾

Sound power: 60 dB (A)

Refrigerant gas: R290

Multifunction remote control

LCD Display

Wheels

FUNCTIONS

Fan only mode

Dehumidification only mode

Auto mode: changes parameters depending on ambient temperature.

Sleep mode: gradually increases the temperature set and ensures reduced noise for greater wellbeing at night.

(1) Rated output power for cooling, EER, Hourly consumption, Energy efficiency class tests (EN 14511)

O2O58			
Nominal cooling capacity (1)	P rated	kW	2,4
Nominal power consumption for cooling (1)	PEER	kW	0,92
Nominal absorption for cooling (1)		A	4,00
Nominal energy efficiency index (1)	EERd		2,6
Energy efficiency class in cooling			A
Energy consumption in "thermostat off" mode	PTO	W	1
Energy consumption in "standby" mode (EN 62301)	PSB	W	0,5
Hourly electricity consumption for single duct (1) cooling mode	QSD	kWh/h	0,90
Supply voltage		V-F-Hz	220/240-1-50
Power supply (min-max)		V	198 / 264
Maximum power consumption in cooling mode (2)		W	1100
Maximum absorption in cooling mode (2)		A	5,6
Dehumidification capacity		l/h	2,6
Air flow (max/med/min)		m ³ /h	394/359/334
Fan speeds		giri/min	3
Flexible pipe (length x diameter)		mm	1500 x 130
Maximum remote control range (distance / angle)		m / °	8 / ±80°
Dimensions (W x H x D) (without packaging)		mm	693 x 665 x 276
Dimensions (W x H x D) (with packaging)		mm	770 x 865 x 421
Weight (without packing)		Kg	37
Weight (with packaging)		kg	44
Sound power level (indoor only) (EN 12102)	LWA	dB(A)	60
Sound pressure level (min-max) (3)		dB(A)	45-49
Degree of protection provided by covers			IPX0
Refrigerant gas		Type	R290
Global warming potential	GWP	kgCO ₂ eq.	3
Lower flammable limit	LFL	kg/m ³	0,038
Refrigerant gas charge		Kg	0,23
Maximum operating pressure		MPa	2,60
Minimum floor area for installation, use and storage		m ²	12
Power cable (N° pole x section m2)			3 x 1,5
Fuse			10AT

OPERATIONAL LIMITS		
Indoor Ambient Temperature	Maximum temperature in cooling	DB 35°C - WB 32°C
Indoor ambient temperature	Minimum temperature in cooling	DB 16°C
Outdoor Ambient Temperature	Maximum temperature in cooling	DB 43°C - WB 32°C
Outdoor ambient temperature	Minimum temperature in cooling	DB 18°C - WB 16°C

(1) Rated output power for cooling, EER, Hourly consumption, Energy efficiency class tests (EN 14511)

(2) High load test in cooling mode

(3) The sound pressure level is been measured into half-anechoic room far 2 meter from the front of the equipment with a microphone at 1 meter of height