

AQUARIA SLIM 12 P

Compact dehumidifier for controlled comfort



SLIM DESIGN

Only 190 mm thickness.



DIGITAL CONTROL

LED display and digital controls.



REMOVABLE 2.5 L TANK

With integrated practical carrying handle.



EXTREMELY PRACTICAL

Handles and wheels for easy movement



HUMIDITY AND TEMPERATURE CONTROL

Humidity level control and room temperature display.

FEATURES

- Dehumidification capacity: 12 l/24h
- Slim design: Only 190 mm thickness
- Tank capacity: 2,5 lt
- Removable tank: with integrated carrying handle
- Digital control panel
- Humidity and temperature display visualization
- 24 h on-off timer
- Auto Function: sets relative humidity at 60%
- Turbo function: maximum fan speed
- Dry function: continuous dehumidification
- Silent function: minimum fan speed
- Manually adjustable Humidistat
- Continuous draining mode
- Washable antidust filter
- Active carbon filter
- Rear handle
- Practical carrying handles
- Automatic shut-off with full tank
- For rooms up to: 55 m³

		AQUARIA SLIM 12 P
PRODUCT CODE		01957
EAN CODE		8021183019575
Dehumidification capacity (2)	l/24h	12
Heating power	W	-
Power absorption in dehumidification mode (1)	W	168
Nominal absorption in dehumidification mode (1)	A	1,10
Max. power absorption in dehumidification mode (2)	W	190
Max. absorption in dehumidification mode (2)	A	1,25
Max. power absorption in dehumidification mode (U.L.U.)	W	220
Protection level		IP 20
Fan speeds		2
Tank capacity	l	2.5
Air volume (max)	m ³ /h	100
Product dimensions (W x H x D with wheels)	mm	320 x 490 x 185
Gift box Dimensions (W x H x D)	mm	365 x 545 x 245
Noise level	db(A)	≤45
Weight (without packing)	kg	10,5
Weight (with packing)	kg	12
Refrigerant gas		R290
GWP (Global Warming Potential)	kg CO ₂	3
Refrigerant gas charge	kg	0,050
Minimum floor area for installation, use and storage	m ²	4,00
Power cable (N° pole x section mmq)	mm ²	3 X 0.75
Plug		SCHUKO
Power supply	V-F-Hz	220-240 - 1 - 50
Power supply min - max	V	207- 254
Conformity mark		CE
Protection level mark		TUV SUD-GS
Air filter		✓
Carbon filter		✓
Continuous operation with hose		✓
Humidity level power settings		✓
Indoor humidity visualizer		✓
Indoor temperature visualizer		✓
Full tank alarm		✓
Laundry function		✓
Timer		✓
Defrosting device		✓

(1) DB 27°C - WB 21°C (27°C - 60% RH)

(2) DB 32°C - WB 29°C (32°C - 80% RH)