

AQUARIA 22 P

Dehumidifier for high-performances, even at low temperatures



TIMER

Programmable on/off from 1 to 24 hours.



DIGITAL CONTROL

LED display and digital controls.



LAUNDRY MODE

Optimisation of fan speed and dehumidification for quick drying of laundry.



AUTO-DEFROST TECHNOLOGY

Automatic defrosting for efficient operation even at low temperatures.



HUMIDITY AND TEMPERATURE CONTROL

The display can be used to adjust the humidity level, automatic or manual mode, and view the room temperature

FEATURES

- Dehumidification capacity: 22 lt/24h
- Tank capacity: 5,5 lt
- Digital control panel
- LED display Ambient temperature and humidity visualization
- Manual humidistat (20%-90% R.H.)
- Auto mode: keeps relative humidity at optimal level (60% R.H.)
- Programmable on-off timer from 1 to 24h
- Sleep Function: lowest fan speed
- Turbo function: maximum fan speed
- Continuous draining mode
- Autoshut off with full tank
- Autorestart function
- Automatic defrost function
- Washable antidust filter
- Active carbon filter
- For rooms up to: 90 m³

		AQUARIA 22 P
PRODUCT CODE		01970
EAN CODE		8021183019704
Dehumidification capacity (2)	l/24h	22
Heating power	W	-
Power absorption in dehumidification mode (1)	W	320
Nominal absorption in dehumidification mode (1)	A	1,8
Max. power absorption in dehumidification mode (2)	W	380
Max. absorption in dehumidification mode (2)	A	2.0
Max. power absorption in dehumidification mode (U.L.U.)	W	450
Protection level		IP 20
Fan speeds		-
Tank capacity	l	5.5
Air volume (max)	m ³ /h	160
Product dimensions (W x H x D with wheels)	mm	335 x 587 x 240
Gift box Dimensions (W x H x D)	mm	384 x 645 x 294
Noise level	dB(A)	≤45
Weight (without packing)	kg	15
Weight (with packing)	kg	16.5
Refrigerant gas		R290
GWP (Global Warming Potential)	kg CO ₂	3
Refrigerant gas charge	kg	0.085
Minimum floor area for installation, use and storage	m ²	4,00
Power cable (N° pole x section mmq)	mm ³	3 x 0.75
Plug		SCHUKO
Power supply	V-F-Hz	220-240 - 1 - 50
Power supply min - max	V	207- 254
Conformity mark		CE
Protection level mark		TUV SUD-GS
Air filter		✓
Carbon filter		✓
Continuous operation with hose		✓
Humidity level power settings		✓
Indoor humidity visualizer		✓
Indoor temperature visualizer		✓
Full tank alarm		✓
Laundry function		✓
Timer		✓
Defrosting device		✓

(1) DB 27°C - WB 21°C (27°C - 60% RH)

(2) DB 32°C - WB 29°C (32°C - 80% RH)