



Design by King & Miranda

FEATURES SECCOPROF 28

Dehumidification capacity: 28l/24h⁽¹⁾
Tank capacity: 10 l
Digital control
LCD Display
Visible water level
Full tank alarm
Double handle
Wheels
For rooms up to: 220 m³

FEATURES SECCOPROF 38

Dehumidification capacity: 38l/24h⁽¹⁾
Tank capacity: 10 l
Warm gas defrosting
Digital control
LCD Display
Visible water level
Full tank alarm
Double handle
Wheels
For rooms up to: 300 m³



SUPER POWER

The products in the SeccoProf range are extremely powerful, and they can absorb up to 38 l of excess humidity per day, thus allowing to dehumidify large spaces.



NON-STOP OPERATING

The constant condensation disposal, which can be selected on the control panel, allows uninterrupted dehumidification.



DIGITAL CONTROL

Multifunction electronic panel, to set the desired humidity level and activate the Drying mode; moreover, Aquaria is equipped with back-lit LCD display to view humidity level and ambient temperature.



WARM GAS DEFROSTING

Guarantees a constant operation of the compressor, avoiding frequent activation and deactivation periods. It also allows the product to work even near 0°C⁽²⁾.



IRON SHAPE

Its metal frame makes the Seccoprof range solid and corrosion- and impact-resistant.

(1) (32° C – 80 %RH)

(2) Only model SeccoProf 38

		SECCOPROF 28	SECCOPROF 38
		01208	01209
Dehumidification capacity (2)	l/24h	28	38
Power absorption in dehumidification mode (1)	W	450	500
Max. power absorption in dehumidification mode (2)	W	550	585
Fan speed		1	1
Tank capacity	l	10	10
Air volume (max)	m ³ /h	340	350
Dimensions (W x H x D)	mm	310 x 650 x 435	310 x 650 x 435
Gift box Dimensions (W x H x D)	mm	380 x 720 x 500	380 x 720 x 500
Sound level	dB(A)	47	49
Weight	Kg	23	25
Refrigerant gas / Charge	Type / kg	R134A / 0,260	R134A / 0,330
Power supply	V-F-Hz	230 - 1 - 50	230 - 1 - 50
Plug		Schuko	
Power supply min - max	V	198 / 264	198 / 244
Air filter		√	√
Carbon filter			
Fotocatalytic filter			
HEPA filter			
Continuous operation with hose		√	√
Digital control		√	√
Digital Humidostat			
Display LCD		√	√
Indoor humidity visualizer		√	√
Indoor temperature visualizer		√	√
Full tank alarm		√	√
Defrosting device		√	
Mot gas defrosting system			√
Handle		√	√
Wheels		√	√
Tank with push-pull locking			
Tank with Handle			
Visible water level		√	√

(1) DB 27°C - WB 21°C (27°C - 60%RH)
 (2) DB 32°C - WB 29°C (32°C - 80%RH)