

NEW


Italian design by:

Skyyrunner

AQUARIA S1 10 P

The compact 10-litre dehumidifier

Cod. 02060



DOUBLE FILTRATION

Captures the main allergens through the antiodust filter and eliminates unpleasant odours thanks to the integrated activated carbon filter.



ERGONOMIC DESIGN

Easy to move thanks to the side handles and wheels, it features a super compact design for easy positioning, even in the corners of the home



DIGITAL CONTROL

The control panel allows accurate settings and timely control of the air temperature and humidity.

FEATURES

- Dehumidification capacity: 10 l / 24h
- For rooms up to 45 m³
- Tank capacity: 2l
- Noise level 40 dB
- Temperature and humidity indicator
- 1-24h timer
- Semi-transparent removable tank
- Full tank alarm
- Speed: low/medium/high
- Dry function
- Automatic defrosting device
- Wheels for transportation



Technical specifications dehumidifiers

PRELIMINARY DATA		AQUARIA S1 10 P	AQUARIA S1 12 P	AQUARIA S1 14 P	AQUARIA S1 16 P	AQUARIA S1 20 P	AQUARIA S1 24 P
PRODUCT CODE		02060	02061	02062	02063	02064	02065
EAN CODE		8021183020601	8021183020618	8021183020625	8021183020632	8021183020649	8021183020656
Dehumidification capacity (2)	l/24h	10	12	14	16	20	24
Power absorption in dehumidification mode (1)	W	216	216	250	250	390	390
Nominal absorption in dehumidification mode (1)	A	1,20	1,20	1,32	1,32	2,20	2,20
Max. power absorption in dehumidification mode (2)	W	235	235	262	262	485	485
Max. absorption in dehumidification mode (2)	A	1,24	1,24	1,51	1,51	2,60	2,60
Max. power absorption in dehumidification mode (U.L.U.)	W	273	273	350	350	515	515
Protection level		IPX0	IPX0	IPX0	IPX0	IPX0	IPX0
Fan speed		3	3	3	3	3	3
Tank capacity	l	2	2	2	2	5	5
Air volume (max)	m³/h	120	120	120	120	180	180
Product dimensions (W x H x D with wheels)	mm	293 x 487x 218	293 x 487 x 218	293 x 512 x 218	293 x 512 x 218	367 x 610 x 274	367 x 610 x 274
Gift box dimensions (W x H x D)	mm	324 x 518 x 248	324 x 518 x 248	324 x 546 x 248	324 x 546 x 248	421 x 664 x 335	421 x 664 x 335
Noise level	dB(A)	40	40	40	40	38	38
Weight (without packaging)	kg	10,2	10,2	11,0	11,0	14,6	14,6
Weight (with packaging)	kg	10,5	10,5	11,4	11,4	16,1	16,1
Minimum floor area for installation, use and storage	m²	4	4	4	4	4	4
Plug		EU	EU	EU	EU	EU	EU
Power supply	V-F-Hz	220-240 - 1 - 50	220-240 - 1 - 50	220-240 - 1 - 50	220-240 - 1 - 50	220-240 - 1 - 50	220-240 - 1 - 50
Conformity mark		CE	CE	CE	CE	CE	CE
Antidust filter		✓	✓	✓	✓	✓	✓
Carbon filter		✓	✓	✓	✓	✓	✓
HEPA filter		-	-	-	-	✓	✓
Continuous operation with hose		✓	✓	✓	✓	✓	✓
Humidity level power settings		✓	✓	✓	✓	✓	✓
Indoor humidity visualizer		✓	✓	✓	✓	✓	✓
Indoor temperature visualizer		✓	✓	✓	✓	-	-
Full tank alarm		✓	✓	✓	✓	✓	✓
Child lock		-	-	-	-	✓	✓
Oscillation		-	-	-	-	✓	✓
Laundry function		✓	✓	✓	✓	✓	✓
Timer		✓	✓	✓	✓	✓	✓
Defrosting device		✓	✓	✓	✓	✓	✓
Coolant gas		R290	R290	R290	R290	R290	R290
GWP (Global Warming Potential)		3	3	3	3	3	3
Refrigerant gas charge	kg	0,036	0,036	0,043	0,043	0,052	0,052
Integrated wi-fi		-	-	-	-	✓	✓

(1) DB 27°C - WB 21°C (27°C-60%)

(2) DB 30°C - WB 27°C (30°C-80%)

(U.L.U.) DB 32°C - WB 23°C