

NEW

# SECCOPROF

Professional dehumidifiers for large spaces

Cod. 02106

Cod. 02107



## SUPER POWER

Seccoprof is able to absorb up to 40 litres of excess humidity per day, thus allowing the dehumidification of large spaces.



## NON-STOP OPERATING

Continuous condensate drain for non-stop dehumidification, without needing to remove the tank.



## WARM GAS DEFROSTING

Guarantees constant operation of the compressor, avoiding frequent activation and deactivation periods, and also allows operation at temperatures close to 0°C.



## DIGITAL CONTROL

The control panel allows accurate settings and timely control of the air temperature and humidity.

## FEATURES

- Dehumidification capacity: 30l / 24h and 40l / 24h
- For rooms up to 150/200 m<sup>3</sup>
- Tank capacity: 8l
- Noise level 52 dB
- Temperature and humidity indicator
- 1-24h timer
- Removable tank with water level visualisation
- 2 fan speed levels
- Dry and Fan function
- Automatic defrosting device
- Wheels for transportation
- Full tank alarm
- 2 filtering levels (pre-filter / activated carbon filter)



		SECCOPROF 30 P	SECCOPROF 40 P
PRODUCT CODE		02106	02107
EAN CODE		8021183021066	8021183021073
Dehumidification capacity (1)	l/24h	30	40
Power absorption in dehumidification mode (1)	W	560	650
Max. power absorption in dehumidification mode (U.L.U.)	W	620	750
Fan speed		2	2
Tank capacity	l	8	8
Air volume (max)	m³/h	240	240
Sound Pressure	dB(A)	52	52
Dimensions (W x H x D)	mm	312 x 635 x 453	312 x 635 x 453
Gift box dimensions (W x H x D)	mm	356 x 688 x 492	356 x 688 x 492
Weight (without packaging)	kg	24,9	27,2
Weight (with packaging)	kg	26,8	29,0
Refrigerant gas / Charge (kg)		R290 / 0,083	R290 / 0,096
Power supply	V-F-Hz	220-240 - 1 - 50	220-240 - 1 - 50
Plug		Schuko	Schuko
Power supply min - max	V	220-240	220-240
Antidust filter		✓	✓
Carbon filter		✓	✓
HEPA filter		-	-
Continuous operation with hose		✓	✓
Digital control		✓	✓
Humidity level power settings		✓	✓
LCD Display		✓	✓
Indoor humidity visualizer		✓	✓
Indoor temperature visualizer		✓	✓
Full tank alarm		✓	✓
Defrosting device		✓	✓
Mot gas defrosting system		✓	✓
Handle		✓	✓
Wheels		✓	✓
Tank with push-pull locking		-	-
Tank with Handle		-	-
Visible water level		✓	✓

(1) DB 32°C - WB 29°C (32°C-80%)  
(U.L.U.) DB 35°C - WB 31°C (35°C-80%)